



# Herkules® Tank

Technical Guide R1.15

The tank with an incomparable price/performance ratio for overground and underground installations.



03.15 | RURAL | R1.15 GRAF HERKULESTANK

## Applications

- Overground – garden or cellar
- Underground – with support pipe
- Pump chambers
- Septic tanks
- Rainwater harvesting
- Retention / detention

## Product Attributes

- Fibreglass-reinforced material
- Extendable for increased capacity
- Lightweight and practical size
- Long-lasting and durably sealed
- Easy to transport – fits through all doorways (up to 800 mm)
- Can be safely installed in areas of high groundwater

## Approvals/Standards

Patent no. in Europe 0870877 and USA no. 5878

## Quality

ISO 9001:2008 Quality Management Standard

*The go to organisation for civil and rural water product solutions*



The tank with an incomparable price/performance ratio for overground and underground installations.

**Design Specifications**

- Low weight of 30 kg per half shell.
- Shape-matched end connectors and connection surfaces enable volumes of several 10000 ltrs.
- Solid profile sealing (lab-test proven sealing lifetime of more than 25 years)
- Tank dome DN 200 (with telescopic end; 1 metre to be cut on demand)
- Support pipe (for underground installation)

**TABLE 1 Technical Data**

Capacity	1600 Litres
Max Ø	1350 mm
Height	1600 mm
Material	Fibre-glass reinforced PP (UV stable and 100% recyclable)
Weight	approx. 60 kgs
Connections	Each 2 x DN 70, DN 100 and DN 200


Code	Description
UT1600HERK	Tank underground (Herkules) c/w access tube and inner support



**FIG. 1** Long-lasting Durably sealed thanks to solid profile sealing (lab-test proven sealing lifetime of more than 25 years)



**FIG. 2** Extendable Shape-matched end connectors and connection surfaces enable volumes of several 10000 ltrs



**FIG. 3** Easy transport Thanks to low weight of 30 kg per half shell and practical size; fits through all doorways (up to 800 mm)



**FIG. 4** Stackable Easy to transport. Up to 10 chambers per pallet.

**Branches Nationwide** Support Office & Technical Services 09 274 0316

**Disclaimer:** While every effort has been made to ensure that the information in this document is correct and accurate, users of Hynds product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hynds unless expressly stated in any sale and purchase agreement entered into between Hynds and the user.