
Maestro 600mm Hinged Cover & Frame

Technical Guide D16.1

High Performance Class D400 (EN124) Hinged Access Cover System, where durability and sealing against odours, and reducing water ingress are priorities.



Applications

High Intensity traffic environments

Wastewater Networks

Stormwater Networks

Product Attributes

600mm clear opening

Features completely sealed hinge cavity

Special automotive grade EPDM seal for ultimate stability and longevity.

Semi circular seating profile ensures a tight seal that prevents odours escaping, and limits water ingress.


Approvals/Standards

Rated to Class D400 to EN124 – exceeds HN-H0-72 Transit load requirement

AS3996:2019 Class E

Quality

Manufactured to a high standard in Ductile Iron Grade 500/7





Ductile Iron access cover system for use in high intensity traffic environments. Where strength, performance and stability are required, the MAESTRO is the market leader.

Features

- Rated to Class D400 to EN124 exceeds HN-H0-72
 Transit load requirement.
- Secured to frame with three flexible front/rear torsion spring bars.
- Multi purpose keyway allows for opening with pick or bar
 no special tools required.
- Locking key required when using lockable cover.

Accessories

- Personalisation available e.g. council logo.
- Captive Hinge before product installation insert a 12 x 180 mm pin.

H 100 e 52 nacestrae 009 009

FIG. 1 Product Dimensions

Testing

Tested by independent third party laboratory OPUS International Consultants Limited to load rating of 400 kN (40 Tonne Ultimate Design Load) to meet AS3996:2019 Class E, EN124 Class D. Nominal wheel loading 8,000kg.

Dimensions

- Clear Opening 600mm
- Overall Dimension 850mm
- Depth of Frame 100mm

Product Range

| Code | Description |
|-----------------|---|
| DIMHMCFHS | Maestro Hinged and Sealed MH Cover and Frame 600mm |
| DIMHMCFHS-X | Maestro Hinged and Sealed MH Cover and Frame 600mm- X |
| DIMHMLCFHS | Maestro Hinged and Sealed Locking MH Cover and Frame 600mm |
| DIMHMCFTCCSTW | Maestro Hinged and Sealed MH Cover and Frame 600mm Stormwater Tauranga City Council |
| DIMHMCFTCCWW | Maestro Hinged and Sealed MH Cover and Frame 600mm Sewer Tauranga City Council |
| DIMHMCFHSSEWWCC | Maestro Hinged and Sealed MH Cover and Frame 600mm Sewer Wellington City Council |
| DIMHMCFHSSTWCCC | Maestro Hinged and Sealed MH Cover and Frame 600mm Stormwater Wellington City Council |
| DIMHMCFHSSTWNCC | Maestro Hinged and Sealed MH Cover and Frame 600mm Stormwater Nelson City Council |
| DIMHMCFHSWTWNCC | Maestro Hinged and Sealed MH Cover and Frame 600mm Wastewater Nelson City Council |
| DIMHMCFHSSTWCCC | Maestro Hinged and Sealed MH Cover and Frame 600mm Stormwater Christchurch City Council |
| DIMHMCFHSWTWCCC | Maestro Hinged and Sealed MH Cover and Frame 600mm Wastewater Christchurch City Council |
| DIMHMCFHS-S | Replacement Maestro Seal 600mm EPDM |
| DIMHBLKSS | Locking Key for Maestro, Solo, Brio DI MH Cover |

Available Regionally

Tauranga City Council

| Code | Description |
|---------------|--------------------------------------|
| DIMHMCFTCCSTW | Maestro Access Cover Ø600 Stormwater |
| DIMHMCFTCCWW | Maestro Access Cover Ø600 Wastewater |







FIG. 3 DIMHMCFTCCWW

Wellington City Council

| Code | Description |
|-----------------|--------------------------------------|
| DIMHMCFHSSTWWCC | Maestro Access Cover Ø600 Stormwater |
| DIMHMCFHSSEWWCC | Maestro Access Cover Ø600 Wastewater |



FIG. 4 DIMHMCFHSSTWWCC



FIG. 5 DIMHMCFHSSEWWCC

Nelson City Council

| Code | Description |
|-----------------|--------------------------------------|
| DIMHMCFHSSTWNCC | Maestro Access Cover Ø600 Stormwater |
| DIMHMCFHSWTWNCC | Maestro Access Cover Ø600 Wastewater |



FIG. 6 DIMHMCFHSSTWNCC



FIG. 7 DIMHMCFHSWTWNCC

Christchurch City Council

| Code | Description |
|-----------------|--------------------------------------|
| DIMHMCFHSSTWCCC | Maestro Access Cover Ø600 Stormwater |
| DIMHMCFHSWTWCCC | Maestro Access Cover Ø600 Wastewater |



FIG. 8 DIMHMCFHSSTWCCC



FIG. 9 DIMHMCFHSWTWCCC

Branches Nationwide Support Office & Technical Services 0800 93 7473

Disclaimer: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hynds product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hynds unless expressly stated in any sale and purchase agreement entered into between Hynds and the user.



