

Hynds Killing Shed

Technical Guide R5.3

The Hynds killing shed is made from precast concrete and comes fitted with various accessories such as; hanging rail, hose tap (15mm), solid door (aluminium/ steel), shelf and drainhold.



03.22 | RURAL | R5.3 HYNDS KILLING SHED

Applications

Killing Shed

Product Attributes

- Pre-assembled
- Fly Proof
- Water Supply Inside

Quality

Manufactured to ISO 9001
Quality Standards

*We are the supply partner of choice for
New Zealand's rural industry, specialising
in water and infrastructure based solutions.*



The Hynds Killing Shed is made from precast concrete and comes fitted with various accessories such as; hanging rail, hose tap (15mm), solid door (aluminium/steel), shelf and drainhold.

Please note accessories vary depending on location of manufacturer.

Applications

- Killing shed

Features

- Concrete enables shed to maintain lower temperatures
- Lockable
- Pre-assembled
- Will not burn or rust
- Completely fly proof
- Water supply inside for cleaning
- Solid bottom of door to stop dogs and cats

Installation

The shed should be unloaded on to a firm, level site with 75-100mm loose fill to cushion the floor.

Product code	Diameter	Height	Weight	Manufactured
KS2400AM	2670mm	2580mm	5300kg	CHCH
KS2000PF	2200mm	2200mm	5360kg	PAL



FIG. 1 KS2000PF (North Island)



FIG. 2 KS2400AM (South Island)

Branches Nationwide Support Office & Technical Services 09 274 0316

Disclaimer: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hynds product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hynds unless expressly stated in any sale and purchase agreement entered into between Hynds and the user.