



Technical Support Sheet

The Lusit Angle Support System

Technical information to support specification of the Lusit Angle Support System

Introduction

The Lusit retaining wall system is a precast concrete engineered wall suitable for a wide variety of ground retention uses.

Pre-production of units in the factory prior to retaining work commencing on site offers a huge project timesaving benefit and is not dependent on the weather.

The ease and speed of installation of the units also offers a big time saving advantage.

A unique and useful feature is the slightly narrower foot, which allows the wall to be constructed to a moderate convex radius. A much larger concave radius can be achieved.

The wall is manufactured in 1m wide standard units, is available in heights ranging from 1m to 4m and is available for a range of design load cases. (See Tables 1, 2 & 3).

Applications

- Motorway retaining walls
- Garden and terracing retaining walls
- Courtyard retaining walls
- Parking area retaining walls
- Basement retaining walls
- Staircase retaining walls
- Walkway retaining walls
- Pond retaining walls
- Containment bunds
- Silage bins

Features

- Functional and elegant
- Engineered to NZ codes
- High quality
- Durable-100 year design life
- Cost effective
- Versatile, enabling maximum use of valuable land
- Simple and quick installation
- Self-supporting - no propping required
- Minimal labour required
- Saves on construction time of project
- Optimises use of available site space
- Uniform appearance
- Units can be removed and reused if desired

The Lusit Angle Support System

The Lusit Angle Support System was developed in Germany, where it has become a very popular engineered retaining wall solution over the last 30 years. It is now available in New Zealand where it has been reengineered to comply with New Zealand standards, environment and soil conditions, including earthquake loading.

The Lusit retaining wall system is very versatile and can be used in residential, commercial, industrial and reading applications. The Lusit Angle Support System's configuration gives the retaining wall it's structural integrity. The Lusit elements are quick and easy to install, creating a huge time saving advantage over site-built retaining walls. It also eliminates the need for specialist construction staff.

Lusit standard panels are 1m wide, with a 940mm wide footing. A 10mm joint gap is provided. The footing generally has projecting reinforcing which will be lapped with in-situ reinforcing, so that the footing can be extended in-situ to the required length as required by the applied loading. The panels range from 1m high to 4m high, in 200mm increments. If required, panels can be made narrower than 1m as a special. Thicknesses increase from 150mm for the shorter panels to 250mm for the higher panels. The slimness of the units results in savings on concrete and transportation costs.

Design Criteria

Hynds offers a range of standard Lusit wall units suitable for three different load cases, namely:

Light Duty:	Suitable for level backfill behind wall, with a 0-2.5kPa surcharge.
Medium Duty:	Suitable for 0-20 sloping backfill behind wall, with a 2.5-12kPa surcharge.
Heavy Duty:	Suitable for TNZBM 2003 HN-HO loading, including a 3.5kPa surcharge.

In cases where vehicular traffic is allowed, no wheel load should be allowed closer than 1m to the inside edge of the wall.

In designing our standard units to suit the above three load types, we have used the following design parameters, which satisfy NZS 3101:

Concrete:	50MPa
Cover:	40mm
Intended Life:	100 years
Exposure Class:	A2, B1 and B2
Reinforcing:	Grade 500E reinforcing bars and ductile Grade 500E Seismic Mesh compliant with NZS3604:2011 (Timber framed buildings standard), AS/NZS 4671:2001 (Steel Reinforcing Materials Standard) and Department of Building and Housing new standard has applied from Feb 2012.

To withstand earthquake loading an EQ horizontal acceleration coefficient $K_h = 0.2$ (NZBC 81/VM4) has been used - Suitable throughout New Zealand

To conform to the most commonly encountered soil values encountered in New Zealand, Hynds has made the following design assumptions:

Foundation Soils:

(beneath the Foundation Pad)

Minimum bearing capacity Q_{qu} : 150kPa (NZS 3604 Sec 3. Good Ground)

(e.g. stiff SILTS/CLAYS, very stiff SILTS, cohesive fill of

SILTS and CLAYS, or CRUSHED ROCK)

Foundation Pad:

There are three possible foundation options, the first option being the preferred and most common option.

Option 1:

Base layer= 150mm layer compacted GAP 65 hardfill

Middle layer= 50mm mass concrete/ blinding with a compressive strength of 15MPa

Top layer= nominal 25mm layer 40MPa non shrink grout (such as Sika Grout 212)

Option 2:

Base layer= 150mm layer compacted GAP 65 hardfill

Top layer= nominal 25mm layer 3:1 earth moist mortar

Option 3:

Base layer= 150mm layer compacted GAP 65 hardfill

Top layer= 100mm layer sand

Backfill material:

(behind the LAS unit)

Backfill to be GAP65 with 60' max allowable batter with 100Ø novacoil drain behind base of wall

Maximum specific weight of backfill: 18kN/m³

Minimum internal angle of friction ϕ : 28°

If your site specific conditions differ from the above commonly encountered New Zealand soil values and structural conditions, or if you are in any doubt, then you should have the site assessed by a CPEng geotechnical engineer.

Corners:

Corners are not a problem with Lusit retaining wall systems.

For internal corners a blunt 90° corner is formed and the footings do not interfere with each other.

For external corners there are two options- a blunt 90° corner or a mitred 90° corner can be formed. As the footings would interfere with each other, an angled smaller footing is provided.

Transport and Installation:

All LAS Elements are delivered on heavy duty wooden pallets. These should be returned to Hynds for a credit once the units are off-loaded. LAS elements up to a height of 1.6m are generally delivered in an upright position, but higher panels are delivered lying down on their face side.

Unloading at the construction site is the responsibility of the contractor, who must ensure that the equipment that is used (crane, digger, forklift, etc) is rated to lift the units. See Tables 1 to 3 for the weights (masses) of the individual units. The units have 2.5 tonne Reid swiftlift anchors cast into the back face for lifting.

If the unit is fitted with two loops in the back face near the top of the panel (optional), these loops MUST NOT BE USED FOR LIFTING. These loops are only to be used for fitting a 16mm diameter bar through that may be used to ensure that the tops of the units remain flush with one

another during the backfilling and compaction processes.

Unloading:

The LAS units are to be unloaded individually by attaching lifting chains to the 2.5 tonne Reids swiftlift lifting anchors cast into the back face. If the units are to be stored at the construction site, then they should either be stood upright on their feet on level ground or placed lying face down on pallets. Please note that if the units are stored lying down, no more than two units may be placed on top of each other and an appropriate distance packer should be placed between the units. Upright storage is preferred to keep the fair face unblemished.

Erecting:

When erecting the LAS units, the lifting chains should be attached to the two top lifting anchors. A strip of wood may be attached to the rear side head of the unit to ensure that the lifting chains don't damage the head. Also, the foot of the element may be supported by an appropriate elastic support (e.g. an old car tyre) to prevent impact on the footing during installation. The units should be handled in a smooth, controlled manner, as any impact or jerking could damage the units and cause cracking.

The Lusit LAS units are self-supporting, hence no propping is required. Nevertheless the units should be handled with sensible care, as the units are only totally stable once the in-situ portion of the concrete foundation has been cast and the units have been backfilled.

After each unit is installed in position, a permanently elastic joint tape is applied to the centre of the side wall of the unit, prior to aligning the next unit. Hynds recommends Compriband, a bitumen impregnated, waterrepellant strip. The joint width is typically 10mm wide.

Joint sealing:

Once alignment is complete, the joint on the back (soil side) of the units are sealed using a 100mm wide bitumen band.

Anchoring the LAS units:

Once the LAS units have been installed next to each other, they form a continuous retaining structure. To assist in preventing the heads of the units going out of alignment during the backfilling process, the units can be provided with two loops about 300 to 400mm from the top of the units. A 16mmØ bar is threaded through these loops, then the loops are hammered over to firmly secure the bar in place, prior to backfilling and compacting.

External corners:

Given that the foot length on the LAS external corner units (and sometimes also the foot length of the neighbouring units) is shorter, it is often necessary to strengthen and stabilise the corner by placing a layer of site concrete in the corner.


Angle brackets may also be necessary to further stabilise the corner.

Backfilling:

To ensure that water can be drained away from the rear side of the units, it is advisable to install a drainage filter layer as well as an adequately sized subsoil drain.

Only a non-binding, free draining, granular, good quality backfill material should be used (e.g. GAP 65). The backfill should be laid in approximately 150 - 200mm thick layers, with each layer being suitably compacted with lightweight compaction machinery. Any compaction machinery should not generate a load greater than that which the wall has been designed to withstand. The compaction machinery should not be placed closer than 500mm to the back of the wall, to avoid displacement of the units during compaction.

Although there is no required minimum fill to the front of the wall, a minimum depth of 150mm would be considered practical to provide a neat finish and to cover up the foundations.


TABLE 1 Light Duty Panels. Design Loads: 0 - 2.5kPa surcharge with 0° backslope

Code	Wall Height h (m)	Wall Thickness t (mm)	Precast Mass (T)	Precast Footing Length (m)	In-Situ Footing Length (m)	Total Base Width w (m)
LSSL4000250	4.0	250	3.3	1.3	1.7	3.0
LSSL3800250	3.8	250	3.1	1.3	1.3	2.6
LSSL3600250	3.6	250	3.0	1.2	1.2	2.4
LSSL3400250	3.4	250	2.8	1.2	1.0	2.2
LSSL3200250	3.2	250	2.6	1.1	1.0	2.1
LSSL3000250	3.0	250	2.5	1.1	0.9	2.0
LSSL2800250	2.8	250	2.2	0.95	0.95	1.9
LSSL2600200	2.6	200	1.7	0.95	0.75	1.7
LSSL2400200	2.4	200	1.5	0.8	0.8	1.6
LSSL2200200	2.2	200	1.4	0.8	0.6	1.4
LSSL2000200	2.0	200	1.3	0.65	0.6	1.25
LSSL1800150	1.8	150	0.9	0.65	0.45	1.1
LSSL1600150	1.6	150	0.8	0.5	0.5	1.0
LSSL1400150	1.4	150	0.7	0.5	0.4	0.9
LSSL1200150	1.2	150	0.6	0.4	0.4	0.8
LSSL1000150	1.0	150	0.5	0.4	0.3	0.7

Design Parameters:

Concrete: 50MPa
 Cover: 40mm
 Intended Life: 100 years
 Exposure Class: A2,B1,B2

Design Assumptions:

Level backslope with 0 - 2.5kPa surcharge, NO vehicle loading
 Maximum specific weight of backfill: 18kN/m³
 Minimum internal angle of friction ϕ : 28°
 Minimum bearing capacity ϕ_{qu} : 150kPa (NZS 3604 Sec 3. Good Ground)
 Founding material:
 Backfill to be GAP65 with 60° max allowable batter with 100Ø novacoil drain behind base of wall
 EQ horizontal acceleration coefficient $K_h = 0.2$ (NZBC B1/VM4) - Suitable throughout New Zealand
 Generally 4 No. 2.5 tonne swiftlift anchors for lifting




TABLE 2 Medium Duty Panels. Design Loads: 2.5 - 12kPa surcharge OR 0 - 20 ° backslope


Code	Wall Height h (m)	Wall Thickness t (mm)	Precast Mass (T)	Precast Footing Length (m)	In-Situ Footing Length (m)	Total Base Width w (m)
LSSM4000250	4.0	250	3.5	1.6	1.7	3.3
LSSM3800250	3.8	250	3.3	1.6	1.3	2.9
LSSM3600250	3.6	250	3.1	1.4	1.4	2.8
LSSM3400250	3.4	250	2.9	1.4	1.3	2.7
LSSM3200250	3.2	250	2.7	1.3	1.2	2.5
LSSM3000250	3.0	250	2.6	1.3	1.1	2.4
LSSM2800250	2.8	250	2.3	1.1	1.2	2.3
LSSM2600200	2.6	200	1.8	1.1	1.1	2.2
LSSM2400200	2.4	200	1.6	0.95	1.05	2.0
LSSM2200200	2.2	200	1.5	0.95	0.95	1.9
LSSM2000200	2.0	200	1.3	0.8	1.0	1.8
LSSM 1800150	1.8	150	0.9	0.8	0.9	1.7
LSSM 1600150	1.6	150	0.8	0.65	0.95	1.6
LSSM 1400150	1.4	150	0.7	0.65	0.75	1.4
LSSM 1200150	1.2	150	0.6	0.5	0.7	1.2
LSSM 1000150	1.0	150	0.5	0.5	0.5	1.0

Design Parameters:

Concrete: 50MPa
 Cover: 40mm
 Intended Life: 100 years
 Exposure Class: A2,B1,B2

Design Assumptions:

Level backslope with wheel load not closer than 1.0m from internal edge of top of wall OR
 Maximum 20° backslope with no surcharge
 Maximum specific weight of backfill: 18kN/m³
 Minimum internal angle of friction ϕ : 28°
 Minimum bearing capacity ϕ_{qu} : 150kPa (NZS 3604 Sec 3. Good Ground)
 Founding material:
 Backfill to be GAP65 with 60° max allowable batter with 100Ø novacoil drain behind base of wall
 EQ horizontal acceleration coefficient $K_h = 0.2$ (NZBC B1/VM4) - Suitable throughout New Zealand
 Generally 4 No. 2.5 tonne swiftlift anchors for lifting


TABLE 3 Heavy Duty Panels. Design Loads: TNZBM 2003 HN-HO Loads including 3.5kPa surcharge

Code	Wall Height h (m)	Wall Thickness t (mm)	Precast Mass (T)	Precast Footing Length (m)	In-Situ Footing Length (m)	Total Base Width w (m)
LSSH3500250	3.5	250	3.2	1.75	2.95	4.7
LSSH3400250	3.4	250	3.1	1.75	2.75	4.5
LSSH3200250	3.2	250	2.9	1.6	2.7	4.3
LSSH3000250	3.0	250	2.8	1.6	2.3	3.9
LSSH2800250	2.8	250	2.6	1.4	2.2	3.6
LSSH2600200	2.6	200	1.9	1.4	1.9	3.3
LSSH2400200	2.4	200	1.7	1.2	1.8	3.0
LSSH2200200	2.2	200	1.6	1.2	1.5	2.7
LSSH2000200	2.0	200	1.4	1.0	1.4	2.4
LSSH1800150	1.8	150	1.0	1.0	1.1	2.1
LSSH1600150	1.6	150	0.9	0.8	1.1	1.9
LSSH1400150	1.4	150	0.8	0.8	0.9	1.7
LSSH 1200150	1.2	150	0.7	0.6	0.8	1.4
LSSH1000150	1.0	150	0.6	0.6	0.6	1.2

Design Parameters:

Concrete: 50MPa
 Cover: 40mm
 Intended Life: 100 years
 Exposure Class: A2,B1,B2

Design Assumptions:

Level backslope with wheel load not closer than 1.0m from internal edge of top of wall
 Maximum specific weight of backfill: 18kN/m³
 Minimum internal angle of friction ϕ : 28°
 Minimum bearing capacity ϕ_{qu} : 150kPa (NZS 3604 Sec 3. Good Ground)
 Founding material:
 Backfill to be GAP65 with 60° max allowable batter with 100Ø novacoil drain behind base of wall
 Seismic case not included (separate case)
 Generally 4 No. 2.5 tonne swiftlift anchors for lifting

NOTES:

1. Concrete : $f'c = 50\text{MPa}$
 2. Reo : $f_y = \text{Grade 500E}$
 3. Reo Cover : 40mm Min
 4. Min Lap Length : 40 x Bar Dia
 5. Dimensional tolerances : Table 5.1-NZSS3109:1997
 6. Do not re-bend reinforcing steel
 7. Design Loading:
 - 2.6 -12kPa surcharge, or 0 - 20 degree backslope
- Max. specific weight of backfill $\gamma_{\text{max}} = 18\text{kN/m}^3$
Exposure classification B2. Design life 100 years
NZS 3101 Tables 3.1 & 3.6

VOL (m3/unit)=	0.21 to 1.35 m3 (precast portion)
WT (ton/unit)=	0.525 to 3.367 tonnes
CODE =	LSSM1000150 to 4000250

--	--

REV#	REVISION DESCRIPTION:	DATE:	DRAWN
1	FOR CONSTRUCTION	19 SEP 2012	DF
2	FOOT LENGTH CHANGED	20 OCT 2012	DF



other person without
proposals and contracts
copied in any form.
SveTerm's limited

6


Lusit LAS

10

REFERENCE QUOTE NUMBER:	20283	CHECKED: LVE
DRAWN: DF	DESIGN: JBH	SIGNATURE:
SIGNATURE:	SIGNATURE:	DATE:
SCALE: AS SHOWN	Note: Do not scale drawing if in doubt ASK!!	27 AUGUST 2012
PAPER SIZE: A3		REVISION:
DRAWING NUMBER:		2



Alternative foundations on, nominal 25mm 3:1 mortar, lean concrete pad and hardcore



Branches Nationwide *Support Office & Technical Services 09 274 0316*

Disclaimer: While every effort has been made to ensure that the information in this document is correct and accurate, users of Hynds product or information within this document must make their own assessment of suitability for their particular application. Product dimensions are nominal only, and should be verified if critical to a particular installation. No warranty is either expressed, implied, or statutory made by Hynds unless expressly stated in any sale and purchase agreement entered into between Hynds and the user.

hynds.co.nz
0800 93 7473

HYNDS
PIPE SYSTEMS